

# AT1201

HOOD TYPE DISHWASHER - TOTAL POWER 10.1 KW



## PRODUCT DESCRIPTION

### BEST WASH

Stainless steel structure AISI 304. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water. Stainless steel upper and lower wash and rinse arms with particularly shaped jets for keeping them free from solid waste.

**Double stainless steel surface filters** in the tank with an easily removable basket for collecting solid waste.

Temperature thermometer. Possibility to change the cycle parameters.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognizable.

The programmable **THERMOLOCK** system ensures that the rinsing cycle starts only at the temperature of 85°C: the ideal temperature for strongly reducing the bacterial load.

Suitable for line or corner installations. Height-adjustable legs.

Hood lifting thanks to springs.

The washing cycle starts only when the hood is completely closed. The appliance stops working if the hood is lifted by chance.

**Standard equipped** with built-in rinse aid dispenser for the best drying results.

**Standard equipped** with built-in connection for detergent dispenser.

**Standard equipped** with built-in connection for drain pump.

**Standard equipped** with built-in connection for WiFi module.

Wide range of options available **on demand**.

**Standard equipped** with one basket for plates and a basket for cups.

**Brilliant washing results against every type of dirt.** AT1201 combines high power to a customizable cycle, which can be set to match different crockery, stains or inlet water conditions.



## TECHNICAL SPECIFICATIONS

**Width:** 660 mm  
**Depth:** 796 mm  
**Height:** 1445 mm  
**Volume:** 0.86 m<sup>3</sup>  
**Rack dimensions:** 500x500 mm  
**Useful height:** 395  
**Working cycles:** 8  
**Electrical power:** 10.10 kW  
**Electric power:** 230 V / 3 - 400 V / 3+N/ 50-60 Hz  
**Dishes/Hour:** 1080-108

