



DESCRIPTION OF STANDARD UNIT:

- Construction of powder-coated steel
- ABS sides with glass
- Grey bumper
- 3 rows of adjustable shelves, highlighted
- Top lighting
- White lighting
- EPOS ticket strips
- Forced cooling
- Temp. range*: +4 ÷ +10°C
- Automatic water evaporation

OPTIONS:

- Multiplexing
- External condensing unit (AZ)**
- LED lighting
- Light plafond
- Night blind
- Wheels

* Temperature range given for maximum ambient temperature of +25°C and relative humidity 60%.

** Cooling power demand: 1000 W/1mr at evaporating temp. -10°C. Automatic water evaporation on request.

TECHNICAL DETAILS:

Typ /Type: R-1 PC	Długość z bokami* /Length with sides* [mm]	Głębokość /Depth [mm]	Wysokość /Height [mm]	Powierzchnia użytkowa /Useful surface [m ²]	Ciężar /Weight [kg]	Dzienne zużycie energii** /Daily consumption** [kWh/24h]	Moc przyłączeniowa** /Electrical input power** [W]	Moc przyłączeniowa dla AZ** /Electrical input power for AZ** [W]
60/70	600	715	1400±30	0,65	90	12,0	900	70
90/70	900			1,10	115	13,5	1200	100
120/70	1200			1,30	150	14,5	1300	130

* Side: 50mm

** Values are provided for an evaporation temp. of -10°C, condensation temp. of +45°C, ambient temp of +25°C and relative humidity of 60%.

