

## TECHNICAL DATA

TEMP. RANGE [°C]	AMBIENT CONDITIONS [°C/RH]	CAPACITY [l]	DIMENSION S [mm - l x d x h]	NUMBER OF DOORS	NUMBER OF SHELVES	SHELF DIMENSION S [mm]	POWER SUPPLY [V/Hz]	ENERGY CONSUMPTION [kWh/24h]	NET WEIGHT [kg]	INSULATION THICKNESS [mm]	REFRIGERANT
-16...-22	+40/40%	1376	1480 x 830 x 2040	2	6	650x530	230/50	8.8	200	70	R-290

## STANDARD


- Electronic control with digital display of temperature
- Dynamic cooling
- Automatic defrost
- Automatic evaporation of condensate
- Full front doors
- Self-closing door
- Adjustable legs
- Interior made of AISI 304 steel
- Shelf guide
- Metal coated shelves
- Interior adapted to GN containers
- Exterior made of AISI 304 steel
- Tropic version (n/a glass door)
- Mechanical door lock
- Automatic operation of fan
- Dynamic cooling with monoblock
- Magnetic door gasket

## OPCJE

- Innovative food protection technology - TiO2
- Foot opened door pedal
- Adjustable legs made of INOX
- Set of castors
- Shelf guide
- Shelves made of INOX
- Meet hooks bar
- Evaporator defrosting heater
- Temperature recorder
- Sound alarm
- Metal coated shelf
- Interior adapted to 600x400 bakery trays
- Light - neutral colour
- UK plug
- Glass door

## COLORS

Below are the basic color versions of the products we offer. The colors given for illustrative purposes only. In the case other colours from RAL palette are required, this should be individually priced.



**INOX**  
Stainless steel

---

BOLARUS S.A. does not assume any liability concerning the topicality of the data contained in this document. Graphic materials and photos may slightly differ from their actual appearance.

---