

BAKERLUX SHOP.Pro[™]

PRICE LIST

VALID FROM 01-2024





BAKERLUX SHOP.Pro™ MASTER

Convection oven

Convection oven, ideal for baking breakfast and snack products, in particular pastry and frozen bakery ones. Humidity setting, 2 programmable fan speeds and 304 stainless steel cooking chamber. The 7" touch digital panel allows the storage of the cooking programs together with their image and name. Automatic management of the cooking processes (CHEFUNOX) to achieve perfect cooking results even without qualified staff. Ready to be connected to the Internet and use the datadrivencooking.com portal.

Unox Intelligent Performance



ADAPTIVE.Cooking™:

 automatically regulates the cooking parameters to ensure repeatable results

187	
Ē	

SMART.Preheating:

STEAM.Plus:

automatically sets the preheating temperature and duration

AUTO.Soft:

AIR.Plus:

2 speed settings

manages the heat rise to make it more delicate

multiple fans with reverse gear and

Unox Intensive Cooking



rapidly extracts humidity from the cooking chamber

Data Driven Cooking

Check and monitor in real-time the operating conditions of your ovens, create and share new recipes. Artificial intelligence transforms consumption data into useful information and allows you to increase daily profits

creates instant humidity

Manual cooking

— Temperature: 30 °C – 260 °C - Humidity set by 20% Up to 9 cooking steps Programs 384 Programs - CHEFUNOX: choose something - MULTI.TIME: manages up to 10 to cook from the library and the cooking processes at the same time oven will automatically set all the parameters READY.BAKE: ready to use settings with infinite time for a quick start **Technical features** Baking chamber made of high-Baking chamber lighting through Double glass resistance AISI 304 stainless steel LED lights embedded in the door

 Wi-Fi / USB data: download/upload programs



UNO:

	A Automatic opening	A Automat	ic opening
10 600x400	🗲 Electric	🗲 Electric	
Oven model	XEFR-10EU-EMRV	XEFR-10E	EU-EMRV-DR
Tray pitch	75 mm	75 mm	
Frequency	50 / 60 Hz	50 / 60 Hz	
Voltage	380-415V 3N~ 220-240V	3~ 380-415V 3	N~ 220-240V 3~
Electrical power	15,5 kW	15,5 kW	
Dimensions - w x d x h	800 x 811 x 952 mm	800 x 811 x	952 mm
Weight	96 kg	96 kg	
Opening type	Hinge on the left side	Hinge on th	ne left side
Version	-	Equipped w	<i>v</i> ith drain
Energy efficiency	27.1 kWh/day 0 kg CO ₂ /o	lay* 27.1 kWh/d	ay 0 kg CO ₂ /day*
Price	6.800,00 €	6.900,00	€
Optional Hinge on the right side			
		Item XEFR-10EU-EMLV XEFR-10EU-EMLV-DR	Additional pric 140,00 140,00
Lateral supports 8 trays - 94 r	nm pitch		
		Item XUC154	182,00
6 600x400	Automatic opening		182,00
6 600x400 Oven model	-	XUC154	182,00
	F Electric	XUC154	182,00
Oven model	Flectric	XUC154	182,00
Oven model Tray pitch	Flectric XEFR-06EU-EMRV 75 mm	XUC154 Automat Celectrice XEFR-061 75 mm 50 / 60 Hz	182,00
Oven model Tray pitch Frequency	 Electric XEFR-06EU-EMRV 75 mm 50 / 60 Hz 	XUC154 Automat Celectrice XEFR-061 75 mm 50 / 60 Hz	182,00 ic opening EU-EMRV-DR
Oven model Tray pitch Frequency Voltage	Flectric XEFR-06EU-EMRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V	XUC154 ▲ Automat ← Electric XEFR-061 75 mm 50 / 60 Hz 3~ 380-415V 3	182,00 ic opening EU-EMRV-DR N~ 220-240V 3~
Oven model Tray pitch Frequency Voltage Electrical power	 Electric XEFR-06EU-EMRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 10,3 kW 	XUC154 ▲ Automat ← Electric XEFR-061 75 mm 50 / 60 Hz 3~ 380-415V 3 10,3 kW	182,00 ic opening EU-EMRV-DR N~ 220-240V 3~
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h	 Electric XEFR-06EU-EMRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 10,3 kW 800 x 811 x 682 mm 	XUC154 ▲ Automat ← Electric XEFR-06H 75 mm 50 / 60 Hz 3~ 380-415V 3 10,3 kW 800 x 811 x	182,00 ic opening EU-EMRV-DR N~ 220-240V 3~ : 682 mm
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight	 Electric XEFR-06EU-EMRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 10,3 kW 800 x 811 x 682 mm 72 kg 	XUC154 Automat ★ Electric XEFR-061 75 mm 50 / 60 Hz 3~ 380-415V 3 10,3 kW 800 x 811 x 72 kg	182,00 ic opening EU-EMRV-DR N~ 220-240V 3~ 682 mm he left side
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type	 ✓ Electric XEFR-06EU-EMRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side 	XUC154 Automat ✓ Electric XEFR-06H 75 mm 50 / 60 Hz 3~ 380-415V 3 10,3 kW 800 x 811 x 72 kg Hinge on th Equipped w	182,00 ic opening EU-EMRV-DR N~ 220-240V 3~ 682 mm he left side
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type Version	 Electric XEFR-06EU-EMRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side - 	XUC154 Automat ✓ Electric XEFR-06H 75 mm 50 / 60 Hz 3~ 380-415V 3 10,3 kW 800 x 811 x 72 kg Hinge on th Equipped w	182,00 ic opening EU-EMRV-DR N~ 220-240V 3~ 682 mm ic 682 m
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type Version Energy efficiency	Flectric XEFR-06EU-EMRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side - 17.5 kWh/day 0 kg CO ₂ /c	XUC154 Automat F Electric XEFR-06H 75 mm 50 / 60 Hz 3~ 380-415V 3 10,3 kW 800 x 811 x 72 kg Hinge on th Equipped w day* 17.5 kWh/d	182,00 ic opening EU-EMRV-DR N~ 220-240V 3~ 682 mm ic 682 m
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type Version Energy efficiency Price Optional	Flectric XEFR-06EU-EMRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side - 17.5 kWh/day 0 kg CO ₂ /c	XUC154 Automat F Electric XEFR-06H 75 mm 50 / 60 Hz 3~ 380-415V 3 10,3 kW 800 x 811 x 72 kg Hinge on th Equipped w day* 17.5 kWh/d 5.040,00	182,00 ic opening EU-EMRV-DR $N^{-} 220-240V 3^{-}$ 682 mm he left side ith drain $ay 0 kg CO_2/day^{+}$ $I \in I$ Additional prior
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type Version Energy efficiency Price Optional	Flectric XEFR-06EU-EMRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side - 17.5 kWh/day 0 kg CO ₂ /c	XUC154 Automat ✓ Electric XEFR-061 75 mm 50 / 60 Hz 3~ 380-415V 3 10,3 kW 800 x 811 x 72 kg Hinge on th Equipped w day* 17.5 kWh/d	182,00 ic opening EU-EMRV-DR N~ 220-240V 3~ c 682 mm c 70 mm
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type Version Energy efficiency Price Optional Hinge on the right side	Flectric XEFR-06EU-EMRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side - 17.5 kWh/day 0 kg CO₂/c 4.960,00 €	XUC154 Automat F Electric XEFR-06H 75 mm 50 / 60 Hz 3~ 380-415V 3 10,3 kW 800 x 811 x 72 kg Hinge on th Equipped w day* 17.5 kWh/d 5.040,00	182,00 $\stackrel{\circ}{=}$ ic opening EU-EMRV-DR N~ 220-240V 3~ $\stackrel{\circ}{=}$ 682 mm he left side <i>v</i> ith drain ay 0 kg CO ₂ /day* $\stackrel{\circ}{=}$ Additional pric 140,00 $\stackrel{\circ}{=}$
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type Version Energy efficiency Price Optional	Flectric XEFR-06EU-EMRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side - 17.5 kWh/day 0 kg CO₂/c 4.960,00 €	XUC154 Automat F Electric XEFR-06H 75 mm 50 / 60 Hz 3~ 380-415V 3 10,3 kW 800 x 811 x 72 kg Hinge on th Equipped w day* 17.5 kWh/d 5.040,00	EU-EMRV-DR N~ 220-240V 3~ 682 mm he left side vith drain ay 0 kg CO ₂ /day*



	A Automatic opening		A Automatic opening	
4 600x400	🗧 Electric		🗧 Electric	
Oven model	XEFR-04EU-EMRV		XEFR-04EU-EMRV-D	R
Tray pitch	75 mm		75 mm	
Frequency	50 / 60 Hz		50 / 60 Hz	
Voltage	380-415V 3N~ 220-240V 3	3~ 220-240V 1 ⁻	~ 380-415V 3N~ 220-240V 3	3~ 220-240V 1~
Electrical power	6,9 kW		6,9 kW	
Dimensions - w x d x h	800 x 811 x 502 mm		800 x 811 x 502 mm	
Weight	57 kg		57 kg	
Opening type	Hinge on the left side		Hinge on the left side	
Version	-		Equipped with drain	
Energy efficiency	7.9 kWh/day 0 kg CO ₂ /d	ay*	7.9 kWh/day 0 kg CO ₂ /da	ay*
Price	3.550,00 €		3.610,00 €	
Optional Hinge on the right side				
		Item XEFR-04EU-E XEFR-04EU-E		Additional price 140,00 € 140,00 €
Lateral supports 3 trays - 100	mm pitch			
		Item XUC152		Price 276,00 €
	_			
	A Automatic opening			
3 600x400	🕈 Electric			
Oven model	XEFR-03EU-EMRV			
Tray pitch	75 mm			
Frequency	50 / 60 Hz			
Voltage	220-240V 1~			
Electrical power	3,5 kW			
Dimensions - w x d x h	800 x 811 x 427 mm			
Weight	46 kg			
Opening type	Hinge on the left side			
Version	-			
Energy efficiency	6.4 kWh/day 0 kg CO ₂ /d	ay*		
Price	2.830,00 €			
Optional Hinge on the right side		Item		Additional price

XEFR-03EU-EMLV

Additional price 140,00 €



	A Automatic opening		
4 460x330	🗲 Electric		
Oven model	XEFR-04HS-EMRV		
Tray pitch	75 mm		
Frequency	50 / 60 Hz		
Voltage	220-240V 1~		
Electrical power	3,5 kW		
Dimensions - w x d x h	600 x 669 x 502 mm		
Weight	39 kg		
Opening type	Hinge on the left side		
Version	-		
Energy efficiency	6.6 kWh/day 0 kg CO ₂ /	day*	
Price	2.360,00 €		
Optional			
Hinge on the right side		Item	Additional price
		XEFR-04HS-EMLV	140,00 €
Lateral supports 3 trays - 100	mm pitch		
		Item XUC151	Price 56,00 €
	A Automatic opening		
3 460x330	Electric		
Oven model	XEFR-03HS-EMRV		
Tray pitch	75 mm		
Frequency	50 / 60 Hz		
Voltage	220-240V 1~		
Electrical power	3 kW		
Dimensions - w x d x h	600 x 669 x 427 mm		
Weight	36 kg		
Opening type	Hinge on the left side		
Version	-		
Energy efficiency	3.5 kWh/day 0 kg CO ₂ /	dav*	
	5.5 KWI/ddy 0 Kg CO2/		
Price	2.110,00 €	auy	
Price Optional Hinge on the right side		Item	Additional price

XEFR-03HS-EMLV

Additional price 140,00 €



BAKERLUX SHOP.Pro[™] TOUCH

Convection oven

Convection oven, ideal for baking breakfast and snack products, in particular pastry and frozen bakery ones. Humidity setting, 2 programmable fan speeds and 304 stainless steel cooking chamber. The 2,4" touch digital panel allows the storage of 99 programs together with their image and name in order to facilitate work in each sales point. Ready to be connected to the Internet and use the datadrivencooking.com portal.

Unox Intensive Cooking

†††	
((((
))))	

DRY.Plus:

)))) rapidly extracts humidity from the cooking chamber



STEAM.Plus:

creates instant humidity starting from 48 °C



AIR.Plus: multiple fans with reverse gear and 2 speed settings

Data Driven Cooking

Check and monitor in real-time the operating conditions of your ovens, create and share new recipes. Artificial intelligence transforms consumption data into useful information and allows you to increase daily profits

Manual cooking

— Temperature: 30 °C – 260 °C

—— Up to 9 cooking steps

Humidity set by 20%

Programs

_

— 99 Programs

Technical features

 Baking chamber made of high- resistance AISI 304 stainless steel with rounded edges	 Double glass	 Baking chamber lighting through LED lights embedded in the door
 Baking chamber with L-shaped rack rails (only for X*FR-10EU-* and X*FR- 06EU-* models)	 2-speed fan system and high- performance circular heating elements	 Wi-Fi / USB data: download/upload HACCP data

Wi-Fi / USB data: download/upload programs



	A Automatic opening	A Automatic opening	
10 600x400	🗲 Electric	🗲 Electric	
Oven model	XEFR-10EU-ETRV	XEFR-10EU-ETRV-D	R
Tray pitch	75 mm	75 mm	
Frequency	50 / 60 Hz	50 / 60 Hz	
Voltage	380-415V 3N~ 220-240V	3~ 380-415V 3N~ 220-240	IV 3~
Electrical power	15,5 kW	15,5 kW	
Dimensions - w x d x h	800 x 811 x 952 mm	800 x 811 x 952 mm	
Weight	96 kg	96 kg	
Opening type	Hinge on the left side	Hinge on the left side	
Version	-	Equipped with drain	
Energy efficiency	27.1 kWh/day 0 kg CO ₂ /d	ay* 27.1 kWh/day 0 kg CO ₂	/day*
Price	6.300,00 €	6.400,00 €	
Optional Hinge on the right side			
		Item XEFR-10EU-ETLV XEFR-10EU-ETLV-DR	Additional price 140,00 € 140,00 €
Lateral supports 8 trays - 94 r	nm pitch	Item	Price
	🖞 Manual opening	Manual opening	
10 600x400	7 Electric	7 Electric	175
Oven model	XEFR-10EU-ETRV-MT	XEFR-10EU-ETRV-N	ITD
Tray pitch	75 mm	75 mm	
Frequency	50 / 60 Hz	50 / 60 Hz	
Voltage	380-415V 3N~ 220-240V	3~ 380-415V 3N~ 220-240	IV 3~
Electrical power	15,5 kW	15,5 kW	
Dimensions - w x d x h	800 x 811 x 952 mm	800 x 811 x 952 mm	
Weight	96 kg	96 kg	
Opening type	Hinge on the left side	Hinge on the left side	
Version	-	Equipped with drain	
Energy efficiency	27.1 kWh/day 0 kg CO ₂ /d	ay* 27.1 kWh/day 0 kg CO ₂	/day*
Price	5.750,00 €	5.850,00 €	
Optional Hinge on the right side			
ge on alle right slut		Item XEFR-10EU-ETLV-MT XEFR-10EU-ETLV-MTD	Additional price 140,00 € 140,00 €
Lateral supports 8 trays - 94 r	nm pitch	Item	Price
		XUC154	182,00 €



Notes: *Details at the end of the price list.



	A Automatic opening	A Automatic opening	
6 600x400	🗲 Electric	🗲 Electric	
Oven model	XEFR-06EU-ETRV	XEFR-06EU-ETRV-D	R
Tray pitch	75 mm	75 mm	
Frequency	50 / 60 Hz	50 / 60 Hz	
Voltage	380-415V 3N~ 220-240V	3~ 380-415V 3N~ 220-240	V 3~
Electrical power	10,3 kW	10,3 kW	
Dimensions - w x d x h	800 x 811 x 682 mm	800 x 811 x 682 mm	
Weight	72 kg	72 kg	
Opening type	Hinge on the left side	Hinge on the left side	
Version	-	Equipped with drain	
Energy efficiency	17.5 kWh/day 0 kg CO ₂ /d	ay* 17.5 kWh/day 0 kg CO ₂ ,	'day*
Price	4.400,00 €	4.480,00 €	
Optional Hinge on the right side			
		Item XEFR-06EU-ETLV XEFR-06EU-ETLV-DR	Additional price 140,00 € 140,00 €
Lateral supports 5 trays - 94 r	nm pitch	Item	Price
6 600×400	Wanual opening	XUC153	138,00 €
6 600x400 Oven model		7 Electric XEFR-06EU-ETRV-N	חדו
	75 mm	75 mm	שוו
Tray pitch	-		
Frequency	50 / 60 Hz	50 / 60 Hz	
Voltage	380-415V 3N~ 220-240V	I	V 3~
Electrical power	10,3 kW	10,3 kW	
Dimensions - w x d x h	800 x 811 x 682 mm	800 x 811 x 682 mm	
Weight	72 kg	72 kg	
Opening type	Hinge on the left side	Hinge on the left side	
Version	-	Equipped with drain	
Energy efficiency	17.5 kWh/day 0 kg CO ₂ /d	5 5 1 5	'day*
Price	4.050,00 €	4.130,00 €	
Optional			
Hinge on the right side		Item XEFR-06EU-ETLV-MT	Additional price 140,00 €
		XEFR-06EU-ETLV-MTD	140,00 €
Lateral supports 5 trays - 94 r	nm pitch		140,00 € Price



Notes:	
*Details at the end of the price	list.



	A Automatic opening	A Automat	ic opening	
4 600x400	🗲 Electric	🗲 Electric	F Electric	
Oven model	XEFR-04EU-ETRV	XEFR-04	EU-ETRV-DR	
Tray pitch	75 mm	75 mm		
Frequency	50 / 60 Hz	50 / 60 Hz		
Voltage	380-415V 3N~ 220-240V 3~	- 220-240V 1~ 380-415V 3N	J~ 220-240V 3~ 220-240V 1~	
Electrical power	6,9 kW	6,9 kW		
Dimensions - w x d x h	800 x 811 x 502 mm	800 x 811 x	502 mm	
Weight	57 kg	57 kg		
Opening type	Hinge on the left side	Hinge on th	e left side	
Version	-	Equipped w	ith drain	
Energy efficiency	7.9 kWh/day 0 kg CO ₂ /da	y* 7.9 kWh/da	y 0 kg CO ₂ /day*	
Price	3.190,00 €	3.250,00	€	
Optional Hinge on the right side		Item XEFR-04EU-ETLV XEFR-04EU-ETLV-DR	Additional price 140,00 € 140,00 €	
Lateral supports 3 trays - 100	mm pitch	Item XUC152	Price 276,00 €	
	Wanual opening	Wanual opening	谢 Manual opening	
4 600x400	🗲 Electric	🕂 Electric	🗧 Electric	
Oven model	XEFR-04EU-ETDV	XEFR-04EU-ETDP	XEFR-04EU-ETDV-DR	
Tray pitch	75 mm	75 mm	75 mm	
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	
Voltage	380-415V 3N~ 220-240V 3~ 220-240V 1~	380-415V 3N~ 220-240V 3~ 220-240V 1~	/ 380-415V 3N~ 220-240V 3~ 220-240V 1~	
Electrical power	6,9 kW	6,9 kW	6,9 kW	
Dimensions - w x d x h	800 x 811 x 500 mm	800 x 811 x 500 mm	800 x 811 x 500 mm	
Weight	57 kg	57 kg	57 kg	
Opening type	Drop down opening	Drop down opening	Drop down opening	
Version	_	Equipped with pump	Equipped with drain	
Energy efficiency	7.9 kWh/day 0 kg CO ₂ /day		y* 7.9 kWh/day 0 kg CO ₂ /day*	
Energy efficiency Price	7.9 kWh/day 0 kg CO₂/day 2.650,00 €			

Lateral supports 3 trays - 100 mm pitch

Item XUC152 Price 276,00 €



	-
	A Automatic opening
3 600x400	🗲 Electric
Oven model	XEFR-03EU-ETRV
Tray pitch	75 mm
Frequency	50 / 60 Hz
Voltage	220-240V 1~
Electrical power	3,5 kW
Dimensions - w x d x h	800 x 811 x 427 mm
Weight	46 kg
Opening type	Hinge on the left side
Version	-
Energy efficiency	6.4 kWh/day 0 kg CO ₂ /day*
Price	2.540,00 €
Ontional	

Optional Hinge on the right side

Item XEFR-03EU-ETLV Additional price 140,00 €



	I Manual opening	🖐 Manual opening
3 600x400	🗲 Electric	🗲 Electric
Oven model	XEFR-03EU-ETDV	XEFR-03EU-ETDP
Tray pitch	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz
Voltage	220-240V 1~	220-240V 1~
Electrical power	3,5 kW	3,5 kW
Dimensions - w x d x h	800 x 811 x 425 mm	800 x 811 x 425 mm
Weight	46 kg	46 kg
Opening type	Drop down opening	Drop down opening
Version	-	Equipped with pump
Energy efficiency	6.4 kWh/day 0 kg CO ₂ /day*	6.4 kWh/day 0 kg CO ₂ /day*
Price	2.110,00 €	2.130,00 €



	Automatic opening	
4 460x330	🕈 Electric	
Oven model	XEFR-04HS-ETRV	
Tray pitch	75 mm	
Frequency	50 / 60 Hz	
Voltage	220-240V 1~	
Electrical power	3,5 kW	
Dimensions - w x d x h	600 x 669 x 502 mm	
Weight	39 kg	
Opening type	Hinge on the left side	
Version	-	
Energy efficiency	6.6 kWh/day 0 kg CO ₂ /day*	
Price	2.050,00 €	
Optional		
Hinge on the right side	Item	Additional price
	XEFR-	04HS-ETLV 140,00 €
Lateral supports 3 trays - 100	,	
	Item XUC15	Price 1 56,00 €
	Wanual opening	🖐 Manual opening
4 460x330	🗲 Electric	🗲 Electric
Oven model	XEFR-04HS-ETDV	XEFR-04HS-ETDP
Tray pitch	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz
Voltage	220-240V 1~	220-240V 1~
Electrical power	3,5 kW	3,5 kW
Dimensions - w x d x h	600 x 669 x 500 mm	600 x 669 x 500 mm
Weight	39 kg	39 kg
Opening type	Drop down opening	Drop down opening
Version	-	Equipped with pump
Energy efficiency	6.6 kWh/day 0 kg CO ₂ /day*	6.6 kWh/day 0 kg CO₂/day*
Price	1.700,00 €	1.720,00 €
Lateral supports 3 trays - 100	mm nitch	

Item XUC151 Price 56,00 €

Notes XEFR-04HS-* - 4 trays TG305 included. *Details at the end of the price list.



	A Automatic opening
3 460x330	🗲 Electric
Oven model	XEFR-03HS-ETRV
Tray pitch	75 mm
Frequency	50 / 60 Hz
Voltage	220-240V 1~
Electrical power	3 kW
Dimensions - w x d x h	600 x 669 x 427 mm
Weight	36 kg
Opening type	Hinge on the left side
Version	-
Energy efficiency	3.5 kWh/day 0 kg CO₂/day*
Price	1.830,00 €

Optional Hinge on the right side

Item XEFR-03HS-ETLV Additional price 140,00 €



	Wanual opening	🖐 Manual opening
3 460x330	🗲 Electric	🗲 Electric
Oven model	XEFR-03HS-ETDV	XEFR-03HS-ETDP
Tray pitch	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz
Voltage	220-240V 1~	220-240V 1~
Electrical power	3 kW	3 kW
Dimensions - w x d x h	600 x 669 x 425 mm	600 x 669 x 425 mm
Weight	36 kg	36 kg
Opening type	Drop down opening	Drop down opening
Version	-	Equipped with pump
Energy efficiency	3.5 kWh/day 0 kg CO ₂ /day*	3.5 kWh/day 0 kg CO₂/day*
Price	1.540,00 €	1.560,00 €



BAKERLUX SHOP.Pro[™] LED

Convection oven

Convection oven with humidity and 2 programmable fan speeds. Easy-to-use oven, ideal for baking breakfast and snack products, in particular pastry and frozen bakery ones. The digital panel allows the storage of 99 programs with 3 cooking steps plus preheating, 12 of which with immediate access. Rounded stainless steel chamber to facilitate cleaning and ensure maximum hygiene.

Unox Intensive Cooking



DRY.Plus:

rapidly extracts humidity from the cooking chamber



STEAM.Plus:

creates instant humidity starting from 48 °C



AIR.Plus: multiple fans with reverse gear and 2 speed settings

Manual cooking

— Temperature: 30 °C – 260 °C

----- Up to 3 cooking steps

— Humidity set by 20%

Programs

— 99 Programs

Technical features

- Baking chamber made of highresistance AISI 304 stainless steel with rounded edges
- Baking chamber with L-shaped rack rails (only for X*FR-10EU-* and X*FR-06EU-* models)

Double glass

 2-speed fan system and highperformance circular heating elements Baking chamber lighting through LED lights embedded in the door



	Manual opening	Manual opening
10 600x400	🗧 Electric	🗲 Electric
Oven model	XEFR-10EU-ELRV	XEFR-10EU-ELRV-DR
Tray pitch	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz
Voltage	380-415V 3N~ 220-240V 3~	380-415V 3N~ 220-240V 3~
Electrical power	15,5 kW	15,5 kW
Dimensions - w x d x h	800 x 811 x 952 mm	800 x 811 x 952 mm
Weight	96 kg	96 kg
Opening type	Hinge on the left side	Hinge on the left side
Version	-	Equipped with drain
Energy efficiency	27.1 kWh/day 0 kg CO ₂ /day*	z 27.1 kWh/day 0 kg CO₂/day*
Price	5.200,00 €	5.300,00 €
Optional Hinge on the right side		
	XI	em Additional p EFR-10EU-ELLV 140,0 EFR-10EU-ELLV-DR 140,0
Lateral supports 8 trays - 94 r	nm pitch Ite	em P
6 600×400	Wanual opening	Manual opening
6 600x400	F Electric	F Electric
Oven model	Flectric	Flectric XEFR-06EU-ELRV-DR
Oven model Tray pitch	Electric XEFR-06EU-ELRV 75 mm	Electric XEFR-06EU-ELRV-DR 75 mm
Oven model Tray pitch Frequency	 Electric XEFR-06EU-ELRV 75 mm 50 / 60 Hz 	Flectric XEFR-06EU-ELRV-DR 75 mm 50 / 60 Hz
Oven model Tray pitch Frequency Voltage	Electric XEFR-06EU-ELRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~	Flectric XEFR-06EU-ELRV-DR 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~
Oven model Tray pitch Frequency Voltage Electrical power	 Electric XEFR-06EU-ELRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 1033 kW 	▶ Electric XEFR-06EU-ELRV-DR 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 10,3 kW
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h	 Electric XEFR-06EU-ELRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 1033 kW 800 x 811 x 682 mm 	Flectric XEFR-06EU-ELRV-DR 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 10,3 kW 800 x 811 x 682 mm
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight	 Electric XEFR-06EU-ELRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 1033 kW 800 x 811 x 682 mm 72 kg 	Flectric XEFR-06EU-ELRV-DR 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 10,3 kW 800 x 811 x 682 mm 72 kg
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h	 Electric XEFR-06EU-ELRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 1033 kW 800 x 811 x 682 mm 	Flectric XEFR-06EU-ELRV-DR 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type	 Electric XEFR-06EU-ELRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 1033 kW 800 x 811 x 682 mm 72 kg 	Flectric XEFR-06EU-ELRV-DR 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side Equipped with drain
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type Version	 Electric XEFR-06EU-ELRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 1033 kW 800 x 811 x 682 mm 72 kg Hinge on the left side - 	Flectric XEFR-06EU-ELRV-DR 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side Equipped with drain
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type Version Energy efficiency Price Optional	 Felectric XEFR-06EU-ELRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 1033 kW 800 x 811 x 682 mm 72 kg Hinge on the left side - 17.5 kWh/day 0 kg CO₂/day⁴ 3.700,00 € 	Flectric XEFR-06EU-ELRV-DR 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side Equipped with drain r 17.5 kWh/day 0 kg CO₂/day* 3.780,00 €
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type Version Energy efficiency	 ✓ Electric XEFR-06EU-ELRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 1033 kW 800 x 811 x 682 mm 72 kg Hinge on the left side - 17.5 kWh/day 0 kg CO₂/day⁴ 3.700,00 € 	Flectric XEFR-06EU-ELRV-DR 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side Equipped with drain r 17.5 kWh/day 0 kg CO₂/day* 3.780,00 €
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type Version Energy efficiency Price Optional Hinge on the right side	Flectric XEFR-06EU-ELRV 75 mm 50 / 60 Hz 380-415∨ 3N~ 220-240∨ 3~ 1033 kW 800 x 811 x 682 mm 72 kg Hinge on the left side - 17.5 kWh/day 0 kg CO ₂ /day ⁴ 3.700,00 € Ite	Flectric XEFR-06EU-ELRV-DR 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side Equipped with drain 417.5 kWh/day 0 kg CO₂/day* 3.780,00 €
Oven model Tray pitch Frequency Voltage Electrical power Dimensions - w x d x h Weight Opening type Version Energy efficiency Price Optional	Flectric XEFR-06EU-ELRV 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 1033 kW 800 x 811 x 682 mm 72 kg Hinge on the left side - 17.5 kWh/day 0 kg CO₂/day* 3.700,00 €	Flectric XEFR-06EU-ELRV-DR 75 mm 50 / 60 Hz 380-415V 3N~ 220-240V 3~ 10,3 kW 800 x 811 x 682 mm 72 kg Hinge on the left side Equipped with drain r 17.5 kWh/day 0 kg CO₂/day* 3.780,00 €



	谢 Manual opening	🖤 Manual opening	谢 Manual opening
4 600x400	🗲 Electric	🗲 Electric	左 Electric
Oven model	XEFR-04EU-ELDV	XEFR-04EU-ELDP	XEFR-04EU-ELDV-DR
Tray pitch	75 mm	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Voltage	380-415V 3N~ 220-240V 3~ 220-240V 1~	380-415V 3N~ 220-240V 3~ 220-240V 1~	380-415V 3N~ 220-240V 3~ 220-240V 1~
Electrical power	6,9 kW	6,9 kW	6,9 kW
Dimensions - w x d x h	800 x 811 x 500 mm	800 x 811 x 500 mm	800 x 811 x 500 mm
Weight	57 kg	57 kg	57 kg
Opening type	Drop down opening	Drop down opening	Drop down opening
Version	-	Equipped with pump	Equipped with drain
Energy efficiency	7.9 kWh/day 0 kg CO ₂ /day ³	* 7.9 kWh/day 0 kg CO ₂ /day ^a	* 7.9 kWh/day 0 kg CO ₂ /day*
Price	2.470,00 €	2.490,00 €	2.530,00 €

Lateral supports 3 trays - 100 mm pitch

Item XUC152 Price 276,00 €



	🖐 Manual opening	🖐 Manual opening
3 600x400	🗲 Electric	🗲 Electric
Oven model	XEFR-03EU-ELDV	XEFR-03EU-ELDP
Tray pitch	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz
Voltage	220-240V 1~	220-240V 1~
Electrical power	3,5 kW	3,5 kW
Dimensions - w x d x h	800 x 811 x 425 mm	800 x 811 x 425 mm
Weight	46 kg	46 kg
Opening type	Drop down opening	Drop down opening
Version	-	Equipped with pump
Energy efficiency	6.4 kWh/day 0 kg CO ₂ /day*	6.4 kWh/day 0 kg CO ₂ /day*
Price	1.930,00 €	1.950,00 €



	🖐 Manual opening	🖐 Manual opening
4 460x330	🗲 Electric	🗲 Electric
Oven model	XEFR-04HS-ELDV	XEFR-04HS-ELDP
Tray pitch	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz
Voltage	220-240V 1~	220-240V 1~
Electrical power	3,5 kW	3,5 kW
Dimensions - w x d x h	600 x 669 x 500 mm	600 x 669 x 500 mm
Weight	39 kg	39 kg
Opening type	Drop down opening	Drop down opening
Version	-	Equipped with pump
Energy efficiency	6.6 kWh/day 0 kg CO ₂ /day*	6.6 kWh/day 0 kg CO ₂ /day*
Price	1.520,00 €	1.540,00 €

Lateral supports 3 trays - 100 mm pitch

Item XUC152 Price 276,00 €



3 460x330	 Manual opening Electric 	Manual opening Electric
Oven model	XEFR-03HS-ELDV	XEFR-03HS-ELDP
Tray pitch	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz
Voltage	220-240V 1~	220-240V 1~
Electrical power	3 kW	3 kW
Dimensions - w x d x h	600 x 669 x 425 mm	600 x 669 x 425 mm
Weight	36 kg	36 kg
Opening type	Drop down opening	Drop down opening
Version	-	Equipped with pump
Energy efficiency	3.5 kWh/day 0 kg CO₂/day*	3.5 kWh/day 0 kg CO ₂ /day*
Price	1.360,00 €	1.380,00 €

BAKERLUX SHOP.Pro[™] MASTER, TOUCH, LED











Oven first-installation kit with manual shower

This kit includes everything you need to install and clean a single oven. Also includes a bottle of SPRAY&Rinse 750ml.

Compatible with	Mandatory	Item	Price
*-DR *-MTD	for the correct installation of a single oven.	ХНС027	415,00 €

Single unit installation kit

This kit includes everything you need to install a single oven, plus a bottle of SPRAY&Rinse 750ml.

Compatible with	Mandatory	Item	Price
*-DR *-MTD	for the correct installation of a single oven.	XUC013	172,00 €

Double stack installation kit

This kit includes everything you need to install and stack two electric ovens.

Compatible with	Mandatory	Item	Price
Oven columns with XEFR-04EU-* (bottom).	for the correct installation of two stacked electric ovens.	XWKQT-04EF-E	310,00 €

Double stack installation kit

It includes all the necessary parts for the correct installation of two stacked electric ovens.

Item	Price
XWKQT-00EF-E	320,00 €



LIEVOX

Prover with boiler steam generator for the precise management of the rising process.

Capacity	8 600x400	Electrical power	2.3 kW	
Tray pitch	68 mm	Voltage	230V 1N~	
Dimensions - w x d x h	800 x 811 x 750 mm	Frequency	50 Hz	
Weight	55 kg	Max. temperature	50 °C	
		Item		Price

XEKPT-08EU-B

1.910,00 €



LIEVOX

Prover controlled from the oven panel.

Capacity	8 600x400	Electrical power	1.2 kW	
Tray pitch	68 mm	Voltage	230V 1N~	
Dimensions - w x d x h	800 x 792 x 866 mm	Frequency	50/60 Hz	
Weight	40 kg	Max. temperature	50 °C	
		Item		Price

XEKPT-08EU-C

1.320,00 €



LIEVOX

Prover with boiler steam generator for the precise management of the rising process.

		Item XEKPT-10EU-B		Price 2.000,00 €
Weight	62 kg	Max. temperature	50 °C	
Dimensions - w x d x h	800 x 809 x 886 mm	Frequency	50 Hz	
Tray pitch	68 mm	Voltage	230V 1N~	
Capacity	10 600x400	Electrical power	2.3 kW	



LIEVOX

Prover controlled from the oven panel.

Capacity	10 600x400	Electrical power	1.2 kW	
Tray pitch	68 mm	Voltage	230V 1N~	
Dimensions - w x d x h	800 x 792 x 866 mm	Frequency	50/60 Hz	
Weight	40 kg	Max. temperature	50 °C	
		Item		Price
		XEKPT-10EU-C	1.44	40,00 €



DECK SHOP.Pro

Static oven with steam generator and integrated digital control.

Capacity	1 600x400	Voltage	220-240V 1N~
Dimensions - w x d x h	800 x 840 x 405 mm	Frequency	50/60 Hz
Weight	61 kg	Max. temperature	290 °C
Electrical power	2.7 kW		
		Item	Price

XEKDT-01EU-S

2.770,00 €



DECK SHOP.Pro

Static oven with digital integrated control

Capacity	1 600x400	Voltage	220-240V 1N~
Dimensions - w x d x h	800 x 840 x 405 mm	Frequency	50/60 Hz
Weight	55 kg	Max. temperature	290 °C
Electrical power	2.7 kW		





Ventless hood

Steam condensing hood. It partially eliminates steam and odours from the cooking fumes. Automatic washing of the integrated condenser.

Dimensions - w x d x h	800 x 863 x 276 mm	Frequency	50/60 Hz
Weight	24 kg	Chimney diameter	121 mm
Electrical power	0.2 kW	Min. air flow	550 m³/h
Voltage	220-240V 1N~	Max. air flow	750 m³/h
		Item	Price

XEKHT-HCEU

1.390,00 €



Waterless Hood

Hood for absorbing the latent heat from the cooking fumes without using water.

Weight	25 kg	Frequency	50/60 Hz
Electrical power	0.1 kW	Chimney diameter	121 mm
		Item	Price
		XEKHT-ACEU	1.330,00 €

Steam condenser

Intermediate cabinet without doors

Closed multi-functional support for safely storing the trays.

4 600x400

70 mm

It eliminates steam and odours from the cooking fumes. It can only be connected to one oven.

		Item		Price
Electrical power	0.008 kW			
Weight	10 kg	Frequency	50/60 Hz	
Dimensions - w x d x h	471 x 320 x 192 mm	Voltage	230V 1N~	



Dimensions - w x d x h

Weight

XEKIT-04EU

Item

605,00 €

Price

640,00 €

800 x 773 x 400 mm

14 kg











High stand

Capacity

Tray pitch

The multifunctional support ideal for storing trays safely and place your oven at the perfect height to work.

Capacity	8 600x400	Dimensions - w x d x h	782 x 675 x 738 mm
Tray pitch	60 mm	Weight	10 kg
		Item	Price
		XEKRT-08EU-H	515,00 €

Intermediate stand

Support for placing the oven at the perfect height for working or for stacking the ovens in a column.

Capacity	6 600x400	Dimensions - w x d x h	794 x 688 x 559 mm
Tray pitch	60 mm	Weight	7 kg
		Item	Price
		XEKRT-06EU-M	490,00 €

Low stand

Support for a column of stacked ovens.

Dimensions - w x d x h	794 x 688 x 355 mm	Weight	6 kg	
		Item		Price
		XWKRT-00EF-L		425,00 €




Floor positioning stand

Mandatory for oven positioning on the floor.

Dimensions - w x d x h	794 x 688 x 150 mm	Weight	4 kg	
Mandatory		Item		Price
for the correct positioning of the oven.		XWKRT-00EF-F		232,00 €





Revolving caster with brake They make cleaning easier. The kit includes 2 wheels with a brake, 2 wheels without a brake, and wall-mounting chains. Wheels must be built on the stand.

	110 mm		
Compatible with Stand, LIEVOX		Item	Price
Sland, LIEVOX		XUC012	268,00 €
Adjustable feet			
Adjustable feet for positi	oning the prover. This kit co	ntains 4 feet.	
Dimensions - h max.	150 mm		
		Item	Price
		XUC045	136,00 €
Feet for ovens			
Feet for positioning over	on counter.		
Dimensions - h	100 mm		
		Item	Price
		XUC035	136,00 €
		XHC016	138,00 €
Water tank			
	tioned on counter. 4 liters c	apacity.	
Water tank for oven posi	tioned on counter. 4 liters c Mandatory	apacity. Item	Price
Water tank for oven posi Compatible with Ovens with pump; Ovens without pump			Price 292,00 €
Water tank for oven posi Compatible with Ovens with pump; Ovens without pump equipped with XHC016.	Mandatory if no water supply is	Item	
Water tank for oven posi Compatible with Ovens with pump; Ovens without pump equipped with XHC016. Water tank	Mandatory if no water supply is	Item XHC021	
Water tank for oven posi Compatible with Ovens with pump; Ovens without pump equipped with XHC016. Water tank Water tank for oven posi	Mandatory if no water supply is available.	Item XHC021	292,00 €
Water tank for oven posi Compatible with Ovens with pump; Ovens without pump equipped with XHC016. Water tank Water tank for oven posi Compatible with Ovens with pump; Ovens without pump	Mandatory if no water supply is available. tioned on stand. 4 liters cap	Item XHC021	
Water tank for oven posi Compatible with Ovens with pump; Ovens without pump equipped with XHC016. Water tank	Mandatory if no water supply is available. tioned on stand. 4 liters cap Mandatory if no water supply is	Item XHC021 Pacity. Item	292,00 € Price
Water tank for oven posi Compatible with Ovens with pump; Ovens without pump equipped with XHC016. Water tank Water tank for oven posi Compatible with Ovens with pump; Ovens without pump equipped with XHC016. Water tank	Mandatory if no water supply is available. tioned on stand. 4 liters cap Mandatory if no water supply is available.	Item XHC021 Pacity. Item	292,00 € Price 192,00 €
Water tank for oven posi Compatible with Ovens with pump; Ovens without pump equipped with XHC016. Water tank Water tank for oven posi Compatible with Ovens with pump; Ovens without pump equipped with XHC016. Water tank	Mandatory if no water supply is available. tioned on stand. 4 liters cap Mandatory if no water supply is available.	Item XHC021 Dacity. Item XHC023	292,00 € Price 192,00 €











Compatible with	Mandatory	Item	Price
Ovens with pump; Ovens without pump equipped with XHC016.	if no water supply is available.	XHC024	254,00 €





Water tank

Water tank to be placed on top of the oven. 6 liters capacity.

Compatible with	Mandatory	Item	Price
Ovens with pump; Ovens without pump equipped with XHC016.	if no water supply is available.	XHC026	138,00 €

Airflow baffle plate

Airflow baffle plate to be applied to the suction fan. It allows you to bake even the most delicate pastry products. Use 1 baffle plate for each fan.

Compatible with	Item	Price
X*FR-04EU-* X*FR-03EU-*	XUC156	28,00 €



PURE

Resin-based filtration system that eliminates all substances that contribute to limescale formation from the water. It filters up to 7.000 litres of water (figure may vary depending on water hardness).

Compatible with	Item	Price
X*FR-10EU-* X*FR-06EU-*	XHC003	328,00 €

REFILL PURE

Replacement cartridge for PURE resin-based filtration system.

Item	Price
XHC004	218,00 €

Price

Price

Price **86,00 €**

75,00 €

128,00 €



BAKERY.PURE

Resin-based filtration system that eliminates all substances that contribute to limescale formation from the water. It filters up to 1.000 litres of water (figure may vary depending on water hardness).

Item

Item XHC011

XHC010

Compatible with X*FR-04*-* X*FR-03*-*

REFILL BAKERY.PURE

Replacement cartridge for PURE resin-based filtration system.

		100	
	-		
- 1			

	di stati



Enhanced buzzer		
Enhanced buzzer to signal t	he end of pre-heating a	ind cooking.
		Item
		XEC015
Wi-Fi connection		
It allows you to wireless con	nect the oven to the int	ernet
Compatible with	Mandatory	Item

Compatible with	Mandatory	Item	Price
MASTER, TOUCH ovens produced before 31/01/202- - e.g. X**T-****	To activate the LONG. 4 Life4 warranty.	XEC012	525,00 €

Ethernet connection

It allows you to connect to connect the oven to the internet via cable

Compatible withMandatoryItemPriceMASTER, TOUCHTo activate the LONG.
Life4 warranty.XEC011405,00 €

BAKERLUX SHOP.Pro[™] MASTER, TOUCH, LED

Accessories 460x330





Double stack installation kit

This kit includes everything you need to install and stack two electric ovens.

Mandatory	Item	Price
for the correct installation of two stacked electric ovens.	XWKQT-00HS-E	288,00 €

LIEVOX

Prover controlled from the oven panel.


		XEKPT-08HS-C		1.060,00 €
		Item		Price
Weight	35 kg	Max. temperature	50 °C	
Dimensions - w x d x h	600 x 711 x 750 mm	Frequency	50/60 Hz	
Tray pitch	68 mm	Voltage	230V 1N~	
Capacity	8 460x330	Electrical power	1.2 kW	



LIEVOX

Prover with boiler steam generator for the precise management of the rising process.

Capacity	8 460x330	Electrical power	2.3 kW	
Tray pitch	68 mm	Voltage	230V 1N~	
Dimensions - w x d x h	600 x 730 x 750 mm	Frequency	50 Hz	
Weight	42 kg	Max. temperature	50 °C	
		Item		Price
		XEKPT-08HS-B		1.710,00 €



Ventless hood

Steam condensing hood. It partially eliminates steam and odours from the cooking fumes. Automatic washing of the integrated condenser.

Dimensions - w x d x h	600 x 731 x 276 mm	Frequency	50/60 Hz	
Weight	21 kg	Chimney diameter	121 mm	
Electrical power	0.2 kW	Min. air flow	550 m³/h	
Voltage	220-240V 1N~	Max. air flow	750 m³/h	
		Item		Price

XEKHT-HCHS **1.240,00 €**

......

Hood with activated carbon filter for built-in solutions.

Dimensions - w x d x h	600 x 697 x 100 mm	Weight	9 kg	
Compatible with		Item		Price
X*FR-04HS-*		XWKHT-BCHS		560,00 €

Waterless Hood

Built-in hood

Hood for absorbing the latent heat from the cooking fumes without using water.

Dimensions - w x d x h	600 x 730 x 232 mm	Voltage	220-240V 1N~
Weight	15 kg	Frequency	50/60 Hz
Electrical power	0.075 kW	Chimney diameter	30 mm
		Item	Price
		XEKHT-ACHS	1.160,00 €



Steam condenser

It eliminates steam and odours from the cooking fumes. It can only be connected to one oven.

Dimensions - w x d x h	471 x 320 x 192 mm	Voltage	230V 1N~	
Weight	10 kg	Frequency	50/60 Hz	
Electrical power	0.008 kW			
		Item		Price

605,00 €













High stand			
The multifunctional	support ideal for storing tra	ys safely and place your oven at th	e perfect height to work.
Capacity	8 460x330	Dimensions - w x d x h	594 x 546 x 738 mm
Tray pitch	60 mm	Weight	8 kg
		Item	Price
		^{Item} XWKRT-08HS-H	
Intermediate st			510,00 €
		XWKRT-08HS-H	510,00 €
Support for placing	the oven at the perfect heig	XWKRT-08HS-H	510,00 €
Support for placing Capacity	the oven at the perfect heig 6 460x330	XWKRT-08HS-H ht for working or for stacking the o Dimensions - w x d x h	510,00 € ovens in a column. 594 x 546 x 559 mm

Floor positioning stand

Mandatory for oven positioning on the floor.

Dimensions - w x d x h	594 x 546 x 150 mm	Weight	4 kg	
		Item		Price
		XWKRT-00HS-F		202,00 €

Revolving caster with brake

They make cleaning easier. The kit includes 2 wheels with a brake, 2 wheels without a brake, and wall-mounting chains. Wheels must be built on the stand.

Dimensions - h	110 mm		
Compatible with		Item	Price
Stand, LIEVOX		XUC012	268,00 €
Feet for ovens			
Feet for positioning over	n on counter.		
Dimensions - h	100 mm		
		Item	Price
		XUC025	136,00 €
Adjustable feet			
Adjustable feet for posit	ioning the prover. This	kit contains 4 feet.	
Dimensions - h max.	150 mm		
		Item	Price

XUC045

Price **136,00 €**



Water supply pump

With this kit, you can use the humidity in the oven, even where there is no water connection. For columns, one pump per oven and/or LIEVOX is required.

Item	Price
XHC016	138,00 €

Water tank

Water tank

Compatible with

Ovens with pump;

Ovens without pump

equipped with XHC016.

Water tank for oven positioned on counter. 4 liters capacity.

Water tank for oven positioned on stand. 4 liters capacity.

Mandatory

available.

if no water supply is

Compatible with	Mandatory	Item	Price
Ovens with pump; Ovens without pump equipped with XHC016.	if no water supply is available.	XHC020	244,00 €

Item

XHC022



Water tank

Water tank for oven positioned on prover. 4 liters capacity. Requires the purchase of XUC012 or XUC045.

Compatible with	Mandatory	Item	Price
Ovens with pump; Ovens without pump equipped with XHC016.	if no water supply is available.	XHC024	254,00 €

Water tank

Water tank to be placed on top of the oven. 6 liters capacity.

Compatible with	Mandatory	Item	Price
Ovens with pump; Ovens without pump equipped with XHC016.	if no water supply is available.	XHC026	138,00 €

Airflow baffle plate

Airflow baffle plate to be applied to the suction fan. It allows you to bake even the most delicate pastry products. Use 1 baffle plate for each fan.

Iter	n Price
XU	C156 28,00 €



BAKERY.PURE

Resin-based filtration system that eliminates all substances that contribute to limescale formation from the water. It filters up to 1.000 litres of water (figure may vary depending on water hardness).

Compatible with X*FR-04*-* X*FR-03*-*	Item XHC010	Price 128,00 €
REFILL BAKERY.PURE		
Replacement cartridge for PURE resin-based	filtration system	

unuye

Price

170,00 €



Enhanced buzzer

Enhanced buzzer to signal the end of pre-heating and cooking.

86,00 €	XEC015		
			Wi-Fi connection
	net	onnect the oven to the inter	It allows you to wireless co
Price	Item	Mandatory	Compatible with
525,00 €	XEC012	To activate the LONG. 24 Life4 warranty.	MASTER, TOUCH ovens produced before 31/01/202 - e.g. X**T-****
		ı	Ethernet connectior
	ernet via cable	connect the oven to the int	It allows you to connect to
Price	Item	Mandatory	Compatible with
405,00 €	XEC011	To activate the LONG.	MASTER, TOUCH

Price

405,00 €

Mandatory	Item
To activate the LONG. Life4 warranty.	XEC011

Item



BAKERLUX SHOP.Pro[™] GO

Convection oven


Programmable easy-to-use convection oven, ideal for baking breakfast and snack products, in particular pastry and frozen bakery ones. The digital panel allows the storage of 99 programs with 3 cooking steps plus preheating, 12 of which with immediate access. Rounded stainless steel chamber to facilitate cleaning and ensure maximum hygiene.

Unox Intensive Cooking



DRY.Plus:

rapidly extracts humidity from the cooking chamber



multiple fans with reverse gear and

Manual cooking

— Temperature: 30 °C – 260 °C

------ Up to 3 cooking steps

Programs

— 99 Programs

Technical features

- Baking chamber made of high-resistance AISI 304 stainless steel with rounded edges
- Baking chamber with L-shaped rack rails (only for X*FR-10EU-* and X*FT-06EU-* models)

Double glass

Baking chamber lighting through LED lights embedded in the door

Convection oven 600x400



UNOS

		Item XEFR-06EU-EGLN	Additional prie
Optional Hinge on the right side			
Price	3.300,00 €	3.380,00 €	
Energy efficiency	17.5 kWh/day 0 kg CO₂/da	ay* 17.5 kWh/day 0 kg CO	₂ /day*
Version	-	Equipped with drain	
Opening type	Hinge on the left side	Hinge on the left side	
Weight	72 kg	72 kg	
Dimensions - w x d x h	800 x 811 x 682 mm	800 x 811 x 682 mm	
Electrical power	10,3 kW	10,3 kW	
Voltage	380-415V 3N~ 220-240V 3	380-415V 3N~ 220-24	0V 3~
Frequency	50 / 60 Hz	50 / 60 Hz	
Tray pitch	75 mm	75 mm	
Oven model	XEFR-06EU-EGRN	XEFR-06EU-EGRN-	DR
6 600x400	 Manual opening Electric 	● Manual opening✓ Electric	
		Item XUC154	Prio 182,00
Lateral supports 8 trays - 94 n	nm pitch	XEFR-10EU-EGLN XEFR-10EU-EGLN-DR	140,00 140,00
Hinge on the right side		Item	Additional prio
Optional			
Price	4.700,00 €	4.800,00 €	J
Energy efficiency	27.1 kWh/day 0 kg CO ₂ /da		₂ /dav*
Version	-	Equipped with drain	
Opening type	Hinge on the left side	Hinge on the left side	
Weight	96 kg	96 kg	
Electrical power	15,5 kW 800 x 811 x 952 mm	15,5 kW 800 x 811 x 952 mm	
Voltage	380-415V 3N~ 220-240V 3		0V 3~
Frequency	50 / 60 Hz	50 / 60 Hz	01/2
Tray pitch -	75 mm	75 mm	
Oven model	XEFR-10EU-EGRN	XEFR-10EU-EGRN-	DR
10 600x400	🗲 Electric	🗲 Electric	
	Manual opening	Wanual opening	

Lateral supports 5 trays - 94 mm pitch

Item XUC153 Price 138,00 €

Convection oven 600x400



	🖐 Manual opening	🖐 Manual opening
4 600x400	🗲 Electric	🗲 Electric
Oven model	XEFR-04EU-EGDN	XEFR-04EU-EGDN-DR
Tray pitch	75 mm	75 mm
Frequency	50 / 60 Hz	50 / 60 Hz
Voltage	380-415V 3N~ 220-240V 3~ 220-240V 1	~ 380-415V 3N~ 220-240V 3~ 220-240V 1~
Electrical power	6,9 kW	6,9 kW
Dimensions - w x d x h	800 x 811 x 500 mm	800 x 811 x 500 mm
Weight	57 kg	57 kg
Opening type	Drop down opening	Drop down opening
Version	-	Equipped with drain
Energy efficiency	7.9 kWh/day 0 kg CO₂/day*	7.9 kWh/day 0 kg CO ₂ /day*
Price	2.230,00 €	2.290,00 €

Lateral supports 3 trays - 100 mm pitch

Item XUC152 Price 276,00 €



	🖞 Manual opening
3 600x400	🗲 Electric
Oven model	XEFR-03EU-EGDN
Tray pitch	75 mm
Frequency	50 / 60 Hz
Voltage	220-240V 1~
Electrical power	3,5 kW
Dimensions - w x d x h	800 x 811 x 425 mm
Weight	46 kg
Opening type	Drop down opening
Version	-
Energy efficiency	6.4 kWh/day 0 kg CO ₂ /day*
Price	1.800,00 €

Convection oven 460x330



4 460x330	Electric
Oven model	XEFR-04HS-EGDN
Tray pitch	75 mm
Frequency	50 / 60 Hz
Voltage	220-240V 1~
Electrical power	3,5 kW
Dimensions - w x d x h	600 x 669 x 500 mm
Weight	39 kg
Opening type	Drop down opening
Version	-
Energy efficiency	6.6 kWh/day 0 kg CO ₂ /day*
Price	1.310,00 €

Item XUC151 Price 56,00 €

Manual opening

Lateral supports 3 trays - 100 mm pitch

	BAR	EREU	X	כ
-000	8		<u>}.</u>	
		S)	ij	
			SHORAY	
	•			

	•
	W Manual opening
3 460x330	🗲 Electric
Oven model	XEFR-03HS-EGDN
Tray pitch	75 mm
Frequency	50 / 60 Hz
Voltage	220-240V 1~
Electrical power	3 kW
Dimensions - w x d x h	600 x 669 x 425 mm
Weight	36 kg
Opening type	Drop down opening
Version	-
Energy efficiency	3.5 kWh/day 0 kg CO₂/day*
Price	1.210,00 €

Accessories 600x400

BAKERLUX SHOP.Pro[™] GO

Accessories 600x400











Oven first-installation kit with manual shower

This kit includes everything you need to install and clean a single oven. Also includes a bottle of SPRAY&Rinse 750ml.

Compatible with	Mandatory	Item	Price
*-DR *-MTD	for the correct installation of a single oven.	ХНС027	415,00 €

Single unit installation kit

This kit includes everything you need to install a single oven, plus a bottle of SPRAY&Rinse 750ml.

Compatible with	Mandatory	Item	Price
*-DR *-MTD	for the correct installation of a single oven.	XUC013	172,00 €

Double stack installation kit

This kit includes everything you need to install and stack two electric ovens.

Compatible with	Mandatory	Item	Price
Oven columns with XEFR-04EU-* (bottom).	for the correct installation of two stacked electric ovens.	XWKQT-04EF-E	310,00 €

Double stack installation kit

It includes all the necessary parts for the correct installation of two stacked electric ovens.

Item	Price
XWKQT-00EF-E	320,00 €

Steam condenser

It eliminates steam and odours from the cooking fumes. It can only be connected to one oven.

Dimensions - w x d x h	471 x 320 x 192 mm	Voltage	230V 1N~
Weight	10 kg	Frequency	50/60 Hz
Electrical power	0.008 kW		
		The sec	Dria

item	Price
XEKCT-HCEH-M	605,00 €



Intermediate cabinet without doors

Closed multi-functional support for safely storing the trays.

Capacity	4 600x400	Dimensions - w x d x h	800 x 773 x 400 mm
Tray pitch	70 mm	Weight	14 kg
		Item	Price
		XEKIT-04EU	640,00 €



High stand

The multifunctional support ideal for storing trays safely and place your oven at the perfect height to work.

Capacity	8 600x400	Dimensions - w x d x h	782 x 675 x 738 mm
Tray pitch	60 mm	Weight	10 kg
		Item	Price
		XEKRT-08EU-H	515,00 €

BAKERLUX SHOP.Pro[™] GO

Accessories 600x400















Intermediate stand

Support for placing the oven at the perfect height for working or for stacking the ovens in a column.

		5	
Capacity	6 600x400	Dimensions - w x d x h	794 x 688 x 559 mm
Tray pitch	60 mm	Weight	7 kg
		Item	Price
		XEKRT-06EU-M	490,00 €
Low stand			
Support for a column of s	stacked ovens.		
Dimensions - w x d x h	794 x 688 x 355 mm	Weight	6 kg
		Item	Price
		XWKRT-00EF-L	425,00 €

Floor positioning stand

Mandatory for oven positioning on the floor.

Dimensions - w x d x h	794 x 688 x 150 mm	Weight	4 kg	
Mandatory		Item		Price
for the correct positioning of the oven.		XWKRT-00EF-F		232,00 €

Revolving caster with brake

They make cleaning easier. The kit includes 2 wheels with a brake, 2 wheels without a brake, and wall-mounting chains. Wheels must be built on the stand.

Dimensions - h	110 mm		
Compatible with		Item	Price
Stand, LIEVOX		XUC012	268,00 €
Feet for ovens			
Feet for positioning ove	en on counter.		
Dimensions - h	100 mm		
		Item	Price
		XUC035	136,00 €
Airflow baffle plat Airflow baffle plate to b Use 1 baffle plate for ea	e applied to the suctior	n fan. It allows you to bake even the mo	ost delicate pastry products.
Compatible with		Item	Price
X*FR-04EU-* X*FR-03EU-*		XUC156	28,00 €

Enhanced buzzer

Enhanced buzzer to signal the end of pre-heating and cooking.

Item	Price
XEC015	86,00 €

Accessories 460x330

BAKERLUX SHOP.Pro[™] GO

Accessories 460x330





Double stack installation kit

This kit includes everything you need to install and stack two electric ovens.

8 460x330

60 mm

Mandatory	Item	Price
for the correct installation of two stacked electric ovens.	XWKQT-00HS-E	288,00 €

Steam condenser

High stand

Capacity

Tray pitch

It eliminates steam and odours from the cooking fumes. It can only be connected to one oven.

		XEKCT-HCEH-M		605,00 €
		Item		Price
Electrical power	0.008 kW			
Weight	10 kg	Frequency	50/60 Hz	
Dimensions - w x d x h	471 x 320 x 192 mm	Voltage	230V 1N~	

The multifunctional support ideal for storing trays safely and place your oven at the perfect height to work.

Dimensions - w x d x h

XWKRT-08HS-H

Weight

Item

594 x 546 x 738 mm

Price

510,00 €

8 kg







Intermediate stand

Support for placing the oven at the perfect height for working or for stacking the ovens in a column.

Capacity	6 460x330	Dimensions - w x d x h	594 x 546 x 559 mm
Tray pitch	60 mm	Weight	6 kg
		Item	Price
		XWKRT-06HS-M	485,00 €
Floor positioning st	and		
Mandatory for oven posit	ioning on the floor.		
Dimensions - w x d x h	594 x 546 x 150 mm	Weight	4 kg
		Item	Price
		XWKRT-00HS-F	202,00 €
Revolving caster wi	th brake		
They make cleaning easie chains. Wheels must be b		with a brake, 2 wheels withou	It a brake, and wall-mounting
Dimensions - h	110 mm		

-	sh
-	

Dimensions - h	110 mm		
Compatible with		Item	
Stand, LIEVOX		XUC012	

Feet for ovens

Feet for positioning oven on counter.

Dimensions - h 100 mm

Item XUC025 Price

268,00 €

BAKERLUX SHOP.Pro[™] GO

Accessories 460x330



Enhanced buzzer

Enhanced buzzer to signal the end of pre-heating and cooking.

Item XEC015 Price **86,00 €**

Accessories 600x400

Tray holder trolleys



Tray holder trolley

Multi-functional support for storing and transporting the trays.

Capacity	18 600x400	Dimensions - w x d x h	726 x 495 x 1700 mm
Tray pitch	80 mm	Weight	15 kg
		Item	Price
		XTB0005	990,00 €



Tray holder trolley

Multi-functional support for storing and transporting the trays.

Capacity	18 400x600	Dimensions - w x d x h	526 x 695 x 1700 mm
Tray pitch	80 mm	Weight	15 kg
		Item	Price
		XTB0003	990,00 €

7777777777777777777777

Baking Essentials









	Height	Item	Price
	27 mm	GRP410	32,00 €
BAKE			
Aluminium tray. It can o	only be ordered in mult	iples of 2 pieces.	
	Height	Item	Price
	15 mm	TG405	*unitary price 32,00 €
BAKE.BLACK			
Non-stick aluminium tra	ay. It can only be order	ed in multiples of 2 pieces.	
	Height	Item	Price
	15 mm	TG460	*unitary price 43,00 €
BAKE.SILICO			
Silicon coated aluminiu	m tray.		
	Height	Item	Price
	9 mm	TG416	47,00 €
CHROMO.GRID			
Flat chromium plated g	rid		
	Height	Item	Price

BAKERLUX SHOP.Pro[™]

Accessories 600x400



FAKIRO.GRILL

Non-stick aluminium tray. Two surfaces - flat and ribbed - for different cookings.

	Height	Item	Price
	12 mm	TG465	225,00 €
FAKIRO™			
Aluminium tray. Two	o surfaces - flat and ribbed	- for different products.	
	Height	Item	Price
	12 mm	TG440	149,00 €
FORO.BAGUET	ГЕ		
Perforated aluminiu	ım tray - 5 channels.		
	Height	Item	Price
	34 mm	TG445	52,00 €
	5		

FORO.BAGUETTE.BLACK

Non-stick perforated aluminium tray - 5 channels .

		,
Price	Item	Height
64,00 €	TG435	34 mm

FORO.BAKE

Perforated aluminium tray. It can only be ordered in multiples of 2 pieces.

Height	Item	Price
15 mm	TG410	*unitary price 37,00 €

FORO.BLACK

Non-stick perforated aluminium tray. It can only be ordered in multiples of 2 pieces.

Height	Item	Price
15 mm	TG430	*unitary price 48,00 €

FORO.SILICO

	Height	Item	Price
	9 mm	TG415	48,00 €
STEEL.BAKE			
Stainless steel tray.			
	Height	Item	Price
	20 mm	TG450	80,00 €

Cooking Essentials



STEAM&FRY

Perforated stainless steel tray for steaming or frying


Height	
30 mm	

Item		
GRP420		

Price 134,00 €

Accessories 460x330

Baking Essentials















1000		1
		L.
1		A
		n

	lated grid - 4 channels. Height	Item	Price
	32 mm	GRP310	28,00 €
			20,00 (
BAKE			
Aluminium tray. It can o	only be ordered in mult	iples of 2 pieces.	
	Height	Item	Price
	11 mm	TG305	*unitary price 19,00 €
BAKE.BLACK			
Non-stick aluminium tr	ay. It can only be order	ed in multiples of 2 pieces.	
	Height	Item	Price
	11 mm	TG370	*unitary price 26,00 €
CHROMO.GRID			
Flat chromium plated g	Irid		
	Height	Item	Price
	8.5 mm	GRP305	19,00 €
FAKIRO™			
Aluminium tray. Two su	ırfaces - flat and ribbed	- for different products.	
	Height	Item	Price
	12 mm	TG335	86,00 €
FORO.BAKE			
Perforated aluminium t	tray. It can only be orde	ered in multiples of 2 pieces.	
	Height	Item	Price
	10 mm	TG310	*unitary price 24,00 €
FORO.BLACK			
Non-stick perforated al	uminium tray. It can or	ly be ordered in multiples of 2 piece	25.
	Height	Item	Price
	10 mm	TG330	*unitary price 32,00 €
FORO.SILICO			
Silicon coated non-stick	< perforated aluminium	i tray.	
	Height	Item	Price
	10 mm	TG314	37,00 €
PAN.FRY			
Non-stick enamelled tra	ay for frying.		
	Height	Item	Price
	height	item	11100

TG350

43,00 €

20 mm

Accessories 460x330



STEAM&FRY

Perforated stainless steel tray for steaming or frying

Height	Item	Price
30 mm	GRP350	97,00 €



SPRAY&Rinse

Practical spray detergent to manually clean all kinds of oven. It degreases and removes all kind of dirt. One box contains n° 12 x 750 ml spray bottles. Trash the bottle once you have used the product. Only for ovens not equipped with integrated automatic washing system.

	Item	Price
1 box	DB1044	111,00 €
6 boxes (unit cost)	DB1044	107,00 €
30 boxes (unit cost)	DB1044	103,00 €

Services

Data Driven Cooking: productivity 4.0



DATA DRIVEN COOKING

Data will be always accessible by smartphone or PC. Data Driven Cooking controls and monitors oven operations in real time, highlighting waste and suggesting usage improvements to reduce consumption. It allows to create and share recipes from one oven to another even remotely.

Create, understand, improve.

Professional Up to 5 connected ovens	Enterprise Unlimited connected ovens
Cooking program management: creation, editing and sending to ovens	Cooking program management: creation, editing and sending to ovens
Ovens management through group and map visualisation	Ovens management through group and map visualisation
Occumentation for HACCP compliance	Occumentation for HACCP compliance
Real-time usage monitoring	Real-time usage monitoring
Push notifications	Push notifications
Community with UNOX Recipe Book	Community with UNOX Recipe Book
S-day analytics data history	Sull analytics data history
	Multi-account access management
	Unox service remote monitoring
	Solution Technical support
Pricing detail Annual fee per group of ovens	Pricing detail Annual fee per group of ovens

Ovens	Price / year VAT excluded	Ovens	Price / year VAT excluded
5	Free	10	500,00 €
		50	2.000,00 €
		100	3.500,00 €
		500	7.000,00 €
		1000	12.000,00 €
		1000 +	Contact sales

Enterprise add-ons

Make the most of DDC Enterprise with add-ons

Enterprise add-on REST API				
	Integration with third party software thanks to Cloud Rest API			
Annual fee per group of ovens				
Ovens	Price / year VAT excluded			
10	50,00 €			
50	200,00 €			
100	350,00 €			
500	700,00 €			
1000	1.200,00 €			
1000 +	Contact sales			

Taking care of our planet is Plan A

More than 30 ENERGY STAR[®]-certified ovens. Why are Unox ovens so efficient?

Thermal insulation

Using the best insulation materials makes it possible to minimize heat loss from the cooking chamber to the outside. The best cooking performance in every situation.

Motor efficiency

The motors in our ENERGY STAR® ovens are designed to heat up as little as possible during each cooking process to cut down on energy waste.

Oven intelligence

Lower water and electricity consumption with every cooking process with an intuitive digital interface and smart technology. Cook efficiently and minimize your environmental impact.

Energy efficiency

The estimate includes only direct emissions produced by the oven. Indirect emissions can be reduced to zero by choosing to purchase energy from renewable sources.

Estimate based on daily use of the oven (300 days/year):

6 light loads of roast chickens (loaded at 20%)

- 1 full load of roast potatoes
- 3 full loads cooking with steam
- 2 hours in an empty oven at 180 °C

Estimated assuming the following weekly washing programs (42 weeks/year):

- 1 long wash
- 1 medium wash



EUROPE

IT - ITALIA UNOX S.p.a E-mail: info@unox.it Tel: +39 049 736 0781

DE - DEUTSCHLAND UNOX DEUTSCHLAND GMBH E-mail: info.de@unox.com Tel: +49 32 211121581

FR - FRANCE, BELGIUM & LUXEMBOURG UNOX FRANCE s.a.s. E-mail: info.fr@unox.com Tel: +33 4 81 68 19 12

PT - PORTUGAL UNOX PORTUGAL E-mail: info.pt@unox.com Tel: +351 918 228 787 IE - IRELAND UNOX IRELAND E-mail: info.ie@unox.com Tel. +353 (0) 87 32 23 218

GB - UNITED KINGDOM

UNOX UK Ltd.

E-mail: info.uk@unox.com

Tel: +44 1252 851 522

UNOX PROFESIONAL ESPAÑA S.L. E-mail: info.es@unox.com Tel: +34 932 20 36 52

ES - ESPAÑA

DK - DENMARK UNOX DANMARK A/S E-mail: info.dk@unox.com Tel: +45 87 91 00 40 CZ - ČESKÁ REPUBLIKA UNOX DISTRIBUTION s.r.o. E-mail: info.cz@unox.com Tel: +420 241 940 000

HR - HRVATSKA UNOX CROATIA E-mail: narudzbe@unox.com Tel: +39 049 86 57 538

TR - TÜRKİYE - UNOX TURKEY Profesyonel mutfak ekipmanlari endüstri ve ticaret limited şirketi E-mail: info.tr@unox.com Tel: +90 530 176 62 03

CH - SWITZERLAND UNOX SWITZERLAND GMBH E-mail: info.ch@unox.com Tel: +41 43 508 61 70 BG - БЪЛГАРИЯ UNOX BULGARIA E-mail: info.bg@unox.com Tel: +359 2 419 05 00

AT - ÖSTERREICH UNOX ÖSTERREICH GMBH E-mail: info.de@unox.com Tel. +43 1 206 092 068

RU - РОССИЯ, ПРИБАЛТИКА И СТРАНЫ СНГ UNOX РОССИЯ E-mail: info.ru@unox.com Tel: +7 (499) 702 - 00 - 14 NL - NETHERLANDS UNOX NETHERLANDS B.V. E-mail: info.nl@unox.com Tel: +31 70 700 6170

PL - POLSKA UNOX POLSKA Sp.zo.o. E-mail: info.pl@unox.com Tel: +48 22 104 17 01

SC - SCANDINAVIAN COUNTRIES UNOX SCANDINAVIA AB E-mail: info.se@unox.com Tel: +46(0)790 75 63 64

AMERICA

US - U.S.A. UNOX Inc. E-mail: info.usa@unox.com Tel: +1 800 489 8669

CA - CANADA UNOX Canada Equipement Professionnel Inc. E-mail: orders.ca@unox.com Tel: +1 800 489 8669

ASIA, OCEANIA & AFRICA

ZA - SOUTH AFRICA UNOX SOUTH AFRICA E-mail: info.za@unox.com Tel: +27 845 05 52 35

AC - OTHER ASIAN COUNTRIES UNOX (ASIA) SDN. BHD E-mail: info.asia@unox.com Tel: +603-58797700

AE - U.A.E. UNOX MIDDLE EAST DMCC E-mail: info.uae@unox.com Tel: +971 4 554 2146 AR - ARGENTINA UNOX ARGENTINA E-mail: info.ar@unox.com Tel: +54 911 37 58 43 46

PH - PHILIPPINES

UNOX PHILIPPINES

E-mail: info.asia@unox.com

Tel: +63 9173108084

TW - TAIWAN,

HONG KONG & MÁCAU

UNOX TAIWAN

E-mail: info.tw@unox.com

Tel: +886 928 250 536

ID - INDONESIA

UNOX INDONESIA

E-mail: info.asia@unox.com

Tel: +62 81908852999

CO - COLOMBIA UNOX COLOMBIA E-mail: info.co@unox.com Tel: +57 305 21 38 223 BR - BRASIL UNOX BRASIL SERVICOS LTDA. E-mail: info.br@unox.com Tel: +55 11 98717-8201 MX - MÉXICO UNOX MÉXICO, S. DE R.L. DE C.V. E-mail: info.mx@unox.com Tel: +52 55 8116-7720

AU - AUSTRALIA UNOX AUSTRALIA PTY Ltd. E-mail: info@unoxaustralia.com.au Tel: +61 3 9876 0803

MY - MALAYSIA & SINGAPORE UNOX (ASIA) SDN. BHD E-mail: info.asia@unox.com Tel: +603-58797700

IN - INDIA UNOX INDIA PRIVATE LIMITED E-mail: info.in@unox.com Tel: +971 4 554 2146

unox.com

UZ - UZBEKISTAN UNOX PRO LLC E-mail: info.uz@unox.com Tel: +998 90 370 90 10

CN - 中华人民共和国 UNOX TRADING (SHANGHAI) Ltd. CO. 电子邮件: info.china@unox.com 电话: #86.21 56907696

VN - VIETNAM UNOX INDOCHINA E-mail: info.asia@unox.com Tel: +84916560803 KR - 대한민국 UNOX KOREA CO. Ltd. 이메일: info.kr@unox.com 전화: +82 2 69410351

NZ - NEW ZEALAND UNOX NEW ZEALAND Ltd.

E-mail: info@unox.co.nz Tel: +64 (0) 800 76 0803



LI1547B1 released 01-2024 Sales conditions: Packaging included - VAT excluded All images used in this price list are for illustrative purposes only.